



ENGINE

Emissions
Model
Maximum Power
PTO Power
Rated Speed
Number of Cylinders - Cubic Capacity
Rate of Compression
Aspiration
Air Filter
Bore x Stroke
Max Torque
Torque Reserve

CLUTCH

Type
Diameter
Lining

TRANSMISSION

Type
Shifting
Gears Forward/Reverse
Speed

PTO SHAFT

Type
Speed

HYDRAULICS

Type
Three Point Linkage
Control - Functions

Lift Capacity
Operating Pressure
Pump Capacity (lt/min)
Hydraulics Valves (number)

OTHER

Drive System
Operating Space
Steering
Service Break
Parking Brake
Front Axle 2WD
Front Axle 4WD
Rear Axle

STANDART BALLAST

Front Ballast
Rear Ballast (Each Wheel)

DIMENSIONS

A-Length
B-Wheelbase
C-Front Track Width
D-Rear Track Width
E-Width
F-Ground Clearance
G-Ground Clearance With Trailer
K-Distance From Muffler
L-Distance From Front to Front Axle Axis
M-Maximum Height
N-Distance From Lowerlink Ends to Rear Axle Axis
Standart Front Tyre
Standart Rear Tyre
Unballasted Tractor Weight
Total Tractor Weight

ROPS

Platform
Cabin

ArmaTrac 1104

Stage III-A (Tier 3)
Perkins 1104d-44ta+ T3059
110 HP (81 KW) @ 2200 rpm
85% of Engine Power
2400 rpm
4,4 Liters/4
18,2:1
Intercooler and Turbocharged
Internal Front Filter Dry Type (With Signal Lights)
105 x 127 mm
416 Nm @ 1400 rpm
18.2%

Dry Type / Mechanical Control
12" (310 mm)
Cerametalic

ZF T-557 L
1-2-3-4, Forward/Reverse, Full Synchronesh
St.
2,02 - 39,30 @ 2400 rpm

Independent, 4 Stepped, Electro-Hydraulics Controlled, (Op: Synchronized)
430-540-750(540E)-1000

Electronic Hydraulics Lifting with Equipment Lifting Handle Sensitivity
Category 2
Electro-Hydraulics Control (Position Control, Depth Control, Sensivity Control, Vibration Isolation, Upper Limit, Sub Limit, Speed Adjustment, Automatic Plow Mode)
5000 kg
190 bar
60 @ 2400 rpm
4 Standart + 4 Locked, Single-Double Effect Transition Valve. (Op: Floating Function)

4WD
Cabin - Platform
Hidrostatic (Open Center - Non Reaction)
In Each Rear Wheel Four Lining Oil Bath Hydraulics Controlled Disc Brake (4x2)
Mechanically Controlled In Each Rear Wheel
-
Carraro
ZF T-557 L Transmission

10x30 kg
4x50 kg

4455 mm
2405 mm
1665-1870 mm
1610-2010 mm
2010-2490 mm
520 mm
415-520 mm
2855 mm
825 mm
2870/2835 mm
1210 mm
360/70R28
480/70R38
4050 kg
5050 kg

YES
YES

The manufacturer, Erkunt Traktör Sanayii A.Ş. realizes continual improvement policy. Therefore, it reserves the right to modify the technical characteristics indicated above without any notice.

Erkunt Traktör Sanayii A.Ş.

Organize Sanayi Bölgesi Batı Hun Cad. No:2 Sincan 06935 Ankara - TR
P: +90 312 267 44 88 (Pbx) F: +90 312 267 44 91
info@armatrac.com - www.armatrac.com