



AXIAL-FLOW[®]

50 SERIES COMBINES

PREVIEW BROCHURE



250 SERIJE SPECIFIKACIJA	AXIAL-FLOW 7250	AXIAL-FLOW 8250	AXIAL-FLOW 9250
Kategorija kombajna	Klasa VII	Klasa VIII	Klasa IX
MOTOR			
Tip - Tier 4 B/Final	Case IH - FPT		
Zapremina motora	11.1 L (677 cu. in.)	12.9 L (787 cu. in.)	16.0 L (970 cu. in.)
Konjska snaga (Nominalna / Maksimalna)	402 KS (299 kW) / 468 KS (349 kW)	480 KS (358 kW) / 555 KS(414 kW)	550 KS (410 kW) / 625 KS (466 kW)
Rast snage	66 KS (49 kW)	75 KS (56 kW)	
Rezervoar za gorivo/ Ad Blue	297 gal. (1 124 L) / 43 gal. (166 L)		317 gal. (1 200 L) / 43 gal. (166 L)
ELEVATOR HEDERA			
Širina Elevatora	54 in. (1 372 mm)		
Dužina elevatora sa/bez Sakupljač kamena	94 in. (2 388 mm)		
Tip pogona elevatora	CVT pogon		
Reverzibilni sistem	CVT hidraulični		
Podizni cilindri hedera	2.95 in. (75 mm) / 3.5 in. (90 mm) / 3.7 in. (95 mm)		
Bočni nagib	+/- 5 stepeni		
Vertikalni nagib Opciono	12 stepeni		
Sakupljač kamena (Opciono)	Sa aktivnim sakupljačem kamena ili bez		
IZVRŠAVANJE/SEPARACIJA			
Tip Izvršavanja	Rotacioni		
Tip pogona rotora/ Prečnik rotora	CVT Pogon / 30 in. (762 mm)		
Brzina rotora	220 – 1180 rpm		
Broj Korpi za izvršaj	2 para		
Ugao zahvata korpi na rotoru	180° / 180°		
Broj korpi za separaciju	2 para		
Sečka Standardno / Opcino	Integrisana sečka / eksterna sečka opciono		

Spiralna sabirna ravan	Ne
Kaskadna Sabirna Ravan	Da
Monitor za kontrolu gubitaka zrna	Standardna oprema
Udarači na rotoru Standardno / Opciono	Manualno podešavanje sa navojnim vretenom / Podešavanje iz kabine

SISTEM ZA ČIŠĆENJE

Širina Sistema za čišćenje	62 in. (1 575 mm)
Ukupna površina sita	10,075 sq. in. (6.9 m ²)
Fiksni sistem ili Samonivelacija sistema za čišćenje	Samonivelacija
Mogućnost čišćenja % stope (Stepeni)	12.1% (7.0°)
Podešavanje otvora sita (Iz kabine / Manuelno)	Standard / N/A
Tip ventilatora za čišćenje/Pogon	CrossFlow / hidraulični
Opseg brzine ventilatora	300 – 1150 rpm
Prečnik Ventilatora	15.4 in. (391 mm)

TRANSPORT I SKLADIŠTENJE

Elevator povratne mase	Trostruki rotacioni udarač		
Elevator čistog zrna (Dimenzije / Kapacitet)	11.9 × 10.4 in. (302 × 264 mm) / 6,500 bu/hr.		
Kapacitet bunkera za zrno Standard / Opciono	315 bu. (11 100 L) / 410 bu. (14 448L)	410 bu. (14 448 L)	
Dužina lule za istovar	28 ft. 9 in. (8.8 m)		
Brzina pražnjenja	4.0 bu. (141 L) u sekundi	4.5 bu. (159 L) u sekundi	

DIMENZIJE

Međuosovinsko rastojanje	147.7 in. (3 752 mm) / 148.5 in. (3 772 mm) - PGA		
Širina	152 in. (3 861 mm)	156 in. (3 962 mm)	
Minimalna težina	42,245 lb. (19 162 kg)	42,845 lb. (19 434 kg)	43,790 lb. (19 863 kg)
Visina kabine	153.5 in. (3 899 mm)	153.7 in. (3 904 mm)	

TEHNOLOGIJA

AFS Connect unapređen sa 2 načina
prenosa datoteka automatizacije
kombajna Standardno/Opciono

Bez automatizacije / AFS Harvest Command



CASE IH
AGRICULTURE
RETHINK PRODUCTIVITY

SAFETY NEVER HURTS![™] Always read the Operators Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

©2018 CNH Industrial America LLC. All rights reserved. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH Industrial America LLC, are the property of those respective companies. Printed in U.S.A. www.caseih.com

CIH18072301