

Model		TG5330	TG5390	TG5470
Engine	Type	Diesel, 3 cylinder, water cooled		Diesel, 4 cylinder, water cooled
	Output (Net (PS @ rpm))	32.0 @ 2600	38.0 @ 2600	46.0 @ 2800
	Displacement (cc)	1498		2197
	Fuel tank capacity (l)	40		50
Transmission	Number of forward speeds	12		
	Forward speed (km/h)	0.37 - 29.82	0.38 - 31.14	0.36-29.06
	Number of reverse speeds	12		
	Reverse speed (km/h)	0.34 - 25.10	0.35-26.21	0.33 - 24.46
	Driven wheels	2WD / 4WD		
	Differential lock	Std. / Pedal		
	Brakes	Wet Disks		
PTO	Type	Clockwise rotation, can be engaged under load		
	Shaft	1 3/8" 6-spline		
	Rotational speed (rpm)	540 - 1000		
Hydraulics	Pump capacity (L/min.)	34.4		43.8
	Position control	Standard		
	Draft control	Standard		
	Rear linkage type	Category 1		
	Lift capacity (kg)	1270		1580
	Steering type	Hydrostatic		
Electrical	Battery (Ah)	55		72
Dimensions	Overall length (mm)	3140		3450
	Overall width (mm)	1480	1500	1560
	Overall height (mm)	2570		2770
	Wheelbase (mm)	1770		1900
	Ground clearance (mm)	420		400
	Weight (kg)	1305	1310	1585
	Agri. tire front	7-16		9.5-16
	Agri. tire rear	12.4 - 24	12.4 - 24	13.6 - 28
	Turf tires front	212/80D-15	212/80D-15	29 x 12.00 - 15
	Turf tires rear	355/80D-20	355/80D-20	475 / 65D - 20