

Model		TH4295			TH4335			TH4365
		Mech		HST	Mech		HST	HST
Engine	Type	Diesel, 3 cylinder, water cooled						
	Output (Net (HP @ rpm))	27.6 @ 2500			31.5 @ 2600			34.7 @ 2600
	Displacement (cc)	1498						1647
	Fuel tank capacity (l)	35						
Transmission	Number of forward speeds	9	8	3	9	8	3	3
	Forward speed (km/h)	2.5 - 23.6	2.1 - 23.6	0 - 25.1	2.6 - 24.5	2.3 - 24.5	0 - 26.1	0 - 26.1
	Number of reverse speeds	3	8	3	3	8	3	3
	Driven wheels	4WD						
	Differential lock	STD						
	Brakes	Wet Disc						
PTO	Type	Independent electric-hydro.						
	Shaft	1 3/8" 6-spline						
	Rear PTO speed (rpm)	0544 @ 2500 1091 @ 2500		0543 @ 2500 1090 @ 2500	0565 @ 2600 1135 @ 2600		0565 @ 2600 1135 @ 2600	0565 @ 2600 1135 @ 2600
	Front PTO speed (rpm)	2000 @ 2500		2000 @ 2500	2080 @ 2600		2080 @ 2600	2080 @ 2600
Hydraulics	Pump capacity (L/min.)	30.8		28.0	32.1		29.2	29.2
	Position control	Standard						
	Rear linkage type	Category 1						
	Lift capacity (kg)	1100						
	Steering type	hydrostatic (power)						
Dimensions with agri. Tire	Overall length (mm)	3125		3095	3125		3095	3095
	Overall width (mm)	1430		1430	1430		1430	1430
	Wheelbase (mm)	1695		1695	1695		1695	1695
	Ground clearance (mm)	220		220	220		220	220
	Weight (kg)	1155	1170	1185	1160	1175	1195	1210
	Agri. tires front	6 - 14						
	Agri. tires rear	12.4 - 16						
	Turf tires front	24 x 8.50 - 12						
	Turf tires rear	315/80D - 16						