

Model		TM3215		TM3245		TM3265	
		Mech	HST	Mech	HST	Mech	HST
Engine	Type	Diesel, 3 cylinder, water cooled					
	Output (Net (PS @ rpm))	19.2 @ 2500		21.6 @ 2500		25.1 @ 2600	
	Displacement (cc)	1123				1498	
	Fuel tank capacity (l)	28					
Transmission	Number of forward speeds	8	3	8	3	8	3
	Forward speed (km/h)	1.5 - 20.1	0-21.1	1.7 - 22.2	0 - 22.2	1.7 - 22.2	0 - 22.2
	Number of reverse speeds	8	3	8	3	8	3
	Driven wheels	4WD					
	Differential lock	STD					
	Brakes	Wet Disc					
PTO	Type	Mechanical	Independent elect.-hydr.	Mechanical	Independent elect.-hydr.	Mechanical	Independent elect.-hydr.
	Shaft	1 3/8" 6-spline					
	Rear PTO speed (rpm)	545 @ 2500	550 @ 2500	567 @ 2600	571 @ 2600	567 @ 2600	571 @ 2600
	Front PTO speed (rpm)	2032 @ 2500	2047 @ 2500	2032 @ 2600	2129 @ 2600	2032 @ 2600	2129 @ 2600
	Pump capacity (L/min.)	20.1			20.9		
Hydraulics	Position control	Standard					
	Rear linkage type	Category 1					
	Lift capacity (kg)	600					
	Steering type	hydrostatic (power)					
	Dimensions	Overall length (mm)	2805				2870
Overall width (mm)		1110					
Wheelbase (mm)		1560					
Ground clearance (mm)		230			250		
Weight (kg)		820	830	825	825	860	865
Agri. tires front		6 - 12		6 - 12		6 - 12	
Agri. tires rear		9.5 - 16		9.5 - 18		9.5 - 18	
Turf tires front		22 x 8.00 - 12		24 x 8.50 - 12		24 x 10.50 - 12	
Turf tires rear		31x 13.50 - 15		315 / 75D - 15		315 / 75D - 15	