

Model		TXG237
Engine	Type	Diesel, 3 cylinder, water cooled
	Output (Gross (kW @ rpm))	16.8 @ 2600
	Output (Gross (HP @ rpm))	22.5 @ 2600
	Displacement (cc)	1123
	Fuel tank capacity (l)	25
Transmission	Type	Hydrostatic
	Number of forward speeds	2
	Forward speed (km/h)	0 - 15.6
	Number of reverse speeds	2
	Reverse speed (km/h)	0 - 11.7
	Driven wheels	2 / 4WD
	Differential lock	Std. / Pedal
	Brakes	Multi wet disk
PTO	Type	Clockwise rotation, can be engaged under load
	Shaft	1 3/8" 6-spline
	Rotational speed of rear (rpm)	540
	Rotational speed of mid (rpm)	2000
Hydraulics	Pump capacity (L/min.)	24
	Position control	Direct control
	Draft control	-
	Rear linkage type	Category 1
	Lift capacity (kg)	540
	Steering type	Power-assisted
Electrical equipment	Battery (Ah)	36
Dimensions	Overall length (mm)	2480
	Overall width (mm)	1210
	Wheelbase (mm)	2280
	Ground clearance (mm)	215
	Weight (kg)	670
	Agri. tires front	18 x 8.50 - 8
	Agri. tires rear	26 x 12.00 - 12
	Turf tires front	18 x 8.50 - 8
	Turf tires rear	26 x 12.00 - 12