

# Specifications

Model			B1830D	B2230D	B2230D-C	B2230HDB	B2230HDB-C	B2530D	B2530D-C	B2530HDB	B2530HDB-C	B3030HDB	B3030HDB-C	
			Gear	Gear		HST		Gear		HST		HST		
Engine	Make		Kubota											
	Model		D905	D1005				D1105				V1505		
	Type		E-TVCS, indirect injection, vertical, liquid-cooled 4-cycle diesel											
	Engine power SAE gross	PS (kW)	18.0 (13.2)	22.0 (16.2)				25.0 (18.4)				30.0 (22.1)		
	Engine power ECE-R24	kW	12.9	14.5				16.1				19.7		
	No. of cylinders		3									4		
	Bore & stroke	mm	72×73.6	76×73.6				78×78.4						
	Total displacement	cm <sup>3</sup>	898	1001				1123				1498		
	Rated speed	rpm	2700											
	Muffler and exhaust pipe		Fully enclosed											
	Air cleaner		Dry paper element (single)											
	Fuel tank capacity	ℓ	28									31		
Drive train	Driving method		4WD											
	Transmission speeds		F9/R9	F9/R9	Infinite (3 ranges)		F9/R9	Infinite (3 ranges)		Infinite (3 ranges)				
	Bi-speed turn		N/A	N/A	Standard		N/A	Standard		Standard				
	Travelling speeds (Forward) km/h		1.1–18.1	1.1–19.1	0–21.3		1.2–20.5	0–22.8		0–23.4				
	Differential lock		Standard											
PTO	Brake type		Wet disc , acting at the rear axle											
	Rear PTO	Type	Transmission driven with sprang clutch			Independent		Transmission driven with sprang clutch		Independent				
		Speed	rpm											
	Mid PTO*	Speed	rpm											
	Mid/Rear separate and simultaneous PTO selection		Standard											
Hydraulic system	Pump capacity	ℓ/min.	35.9											
	Lift control type		Position											
	Lift capacity at link end	kg	970											
	Max. operating pressure	kg/cm <sup>2</sup>	155											
	3-point hitch		Category I											
	Auxiliary remote control valve		1 standard (double acting)											
	Hydraulic outlets		2 places (Mid & Rear)											
	Hydraulic cylinder for mower lifting		Standard on Mower Deck											
Dimensions	Hydrostatic power steering		Standard (full hydraulic type)											
	Overall length (with 3P)	mm	2735	2735	2835	2735	2835	2735	2835	2735	2835	2900	3010	
	Overall width (min. tread)	mm	1025	1105				1095				1365		
	Overall height	mm	2240	2260	2060	2260	2060	2290	2090	2290	2090	2320	2125	
	Wheelbase	mm	1500									1666		
	Tread	Front	mm											
		Rear	800–970				855–1075		850–1095				1050	
	Ground clearance	mm	220	240				270				315		
	Turning radius with brake	m	2.1											
	Standard tyre	Front: Farm / Turf	6-12B/22×8.50-12	6–12 / 22×8.50–12				6.00–12 / 24×8.50–12				7–12 / 24×8.50–12		
		Rear: Farm / Turf	8-16/31×13.5-15	9.5–16 / 31×13.5–15				9.5–18 / 315/75D–15				12.4–16 / 13.6–16		
	Weight	kg	705	720	930	745	955	725	935	750	960	840	1035	
Safety frame			Rear mount foldable ROPS	Rear mount foldable ROPS	Factory Cabin w/ Air-conditioning	Rear mount foldable ROPS	Factory Cabin w/ Air-conditioning	Rear mount foldable ROPS	Factory Cabin w/ Air-conditioning	Rear mount foldable ROPS	Factory Cabin w/ Air-conditioning	Rear mount foldable ROPS	Factory Cabin w/ Air-conditioning	
Alternator capacity			40A											
Options	Ratchet - type lift rod		Option											
	Telescopic stabilisers		Option											
	Telescopic lower - link ends		Option											
	Rear work lamp		-	-	Option	-	Option	-	Option	-	Option	-	Option	
Rear wiper		-	-	Option	-	Option	-	Option	-	Option	-	Option		

The company reserves the right to change the above specifications without notice.

\*Manufacturer's estimate.

Mower deck cannot be attached to the tractor with farm tyre 6.00–12, 9.5–18.

Model availability varies in each country.

©2007 Kubota Corporation



## KUBOTA (Deutschland) GmbH

Senefelder Straße 3 - 5, 63 110 Rodgau/Nieder-Roden  
 Telefon 06106/873-0 Telefax 06106/873197 E-Mail info@kubota.de  
 www.kubota.de