

| | Category | R41 | R50 | R60 |
|--------------------------------|-------------------------------------|---|---------|----------------------------|
| Dimensions & Weight | Overall length, Bumper to link (mm) | 3192 | 3192 | 3192 |
| | Overall width with tires (mm) | 1420 | 1420 | 1420 |
| | Wheelbase (mm) | 1758 | 1758 | 1758 |
| | Ht to top of rops (mm) | 2416 | 2416 | 2416 |
| | Total weight without ballast (kg) | 1733 | 1733 | 1733 |
| Tires | Front | 9.5-16 | 9.5-16 | 9.5-16 |
| | Rear | 12.4-24 | 13.6-24 | 13.6-24 |
| PTO | Type (options) | Independent / GSP | | |
| | Base speed (rpm) | 540/750/1000 | | |
| Hydraulic | Control system (options) | Position / Draft / Auto leveling | | |
| | Remote valves (options) | 4 (front), 2/4/6 (rear) | | |
| Engine | Engine Hp (kW) | 41(30.5) | 47(35) | 56(41.6) |
| | Rated speed (rpm) | 2600 | 2600 | 2600 |
| Traveling system | Transmission Type (options) | Synchro shuttle / EZ-shift / HST | | Synchro shuttle / EZ-shift |
| | No. of speed | 32x16 (Synchro shuttle, EZ-shift) / 3 Range (HST) | | 32x16 |
| | Forward Speed (Km/h) | 0~26.7 | 0~27.1 | 0~27.1 |