

| Category | | U50 ROPS | U50 CABIN | U60 ROPS | U60 CABIN |
|--------------------------------|-------------------------------------|-----------------------|-----------|-------------------------|-----------|
| Dimensions & Weight | Overall length, Bumper to link (mm) | 3434 | 3434 | 3434 | 3434 |
| | Overall width with tires (mm) | 1669 | 1669 | 1699 | 1699 |
| | Wheelbase (mm) | 1930 | 1930 | 2047 | 2047 |
| | Ht to top of rops (mm) | 2598 | 2403 | 2598 | 2426 |
| | Total weight without ballast (kg) | 1952 | 2195 | 1945 | 2200 |
| Tires | Front (options) | 9.5-20 | | 9.5-20 | |
| | Rear | 13.6-28 | | 16/9-24 | |
| PTO | Type (options) | Independent / GSP | | Independent / GSP | |
| | Base speed (rpm) | 540/750/1000 | | 540/750/1000 | |
| Hydraulic | Control system (options) | Position / Draft | | Position / Draft | |
| | Remote valves (options) | 4 (front), 2/4 (rear) | | 4 (front), 2/4/6 (rear) | |
| Engine | Engine Hp(kW) | 47(35) | | 56(41.6) | |
| | Rated speed (rpm) | 2600 | | 2600 | |
| Traveling system | Transmission Type | Synchro shuttle | | Synchro shuttle | |
| | No. of speed | 16x16 | | 16x16 | |
| | Forward Speed (Km/h) | 1.2~27.88 | | 1.2~29.19 | |

Note. Specifications and Designs are subject to change without prior notice.

| Category | | U6020 ROPS | U6020 CABIN | U6030 ROPS | U6030 CABIN |
|--------------------------------|-------------------------------------|-----------------------|-------------|-------------------------|-------------|
| Dimensions & Weight | Overall length, Bumper to link (mm) | 3434 | 3434 | 3434 | 3434 |
| | Overall width with tires (mm) | 1777 | 1777 | 1777 | 1777 |
| | Wheelbase (mm) | 2047 | 2047 | 2047 | 2047 |
| | Ht to top of rops (mm) | 2614 | 2506 | 2614 | 2506 |
| | Total weight without ballast (kg) | 2165 | 2370 | 2165 | 2370 |
| Tires | Front (options) | 11.2-20 | | 11.2-20 | |
| | Rear | 14.9-28 | | 14.9-28 | |
| PTO | Type (options) | Independent / GSP | | Independent / GSP | |
| | Base speed (rpm) | 540/750/1000 | | 540/750/1000 | |
| Hydraulic | Control system (options) | Position / Draft | | Position / Draft | |
| | Remote valves (options) | 4 (front), 2/4 (rear) | | 4 (front), 2/4/6 (rear) | |
| Engine | Engine Hp(kW) | 57(42) | | 62(45.6) | |
| | Rated speed (rpm) | 2500 | | 2500 | |
| Traveling system | Transmission Type | Synchro shuttle | | Synchro shuttle | |
| | No. of speed | 16x16 | | 16x16 | |
| | Forward Speed (Km/h) | 1.2~29.25 | | 1.2~29.25 | |