



Load it up. This versatile loader tractor gets after ANYTHING.



## The New Tier 4i 5600 Series. It has a nose for what you want it to do.

**Visibility is key in loader work.** Our MF5609 and MF5610 each offer a new sloped nose to improve sightline down the hood and beyond the bucket. The Visio roof further improves forward visibility, even at full loader height.



The larger, 6-post cab design provides a sweeping 360° view, as well as a roomier, more comfortable and productive workspace.

Powerful and maneuverable, these tractors are multi-taskers, even in close quarters. The proven Dyna-4<sup>™</sup> transmission has many new features, including AUTO-DRIVE, which automatically and smoothly shifts gears as if driving a car.



Model	5609	5610
PTO power @ 2,200 rpm HP (kW)	70 (52)	75 (56)
Engine power HP (kW)	90 (67)	100 (75)
Engine make/model	33 AWI HD by AGCO Power	
Cylinders/displacement L (CID)	3-cylinder/3.3 (201)	
Aspiration/charge cooling	Turbocharged & intercooled	
Fuel system	Common rail direct injection	
Emissions control	External Exhaust Gas Recirculation (EGR), Diesel Oxidation Catalyst (DOC)	
Fuel capacity gal. (L)	42 (160)	
Transmission		
Type: standard	Dyna-4 transmission with speed	matching; AUTO-DRIVE is optional
Speeds	4 gears, 4 range	es, 16 total speeds
Shuttle	Electro hydraulic via LH 3-function contro	I lever or optional RH factory loader joystick
Creeper	Optional 14:1 reduction	
Rear 3-point Hitch		
Type /ASAE category	Electronic linkage control wit	h lower link draft sensing/Cat II
Lift capacity @ 24" lbs. (kg)	7,100	(3,220)
4wd Front Axle		
Туре	Center Drive with	planetary reduction
Drive engagement	Electro	hydraulic
Rear Axle		
Туре	Flange with inter	nal wet disc brakes
Differential lock	Fully locking e	electro hydraulic
Braking	Independent, interna	l wet multi-disc brakes
Power Take Off (PTO)		
Туре	Independent, ele	ctronically engaged
Speeds	540/540e	540/540e/1,000
Hydraulics		
System type	Oper	center
Standard flow at remotes gpm (Lpm)	15	(57)
Optional flow at remotes gpm (Lpm)	26 (100) with 1	win Flow System
Rear remote valves	2 standard, u	p to 4 available
Loader joystick option	Integrated factory loader joystick	with shuttle control and mid valves
Operator's Area		
Type of operator's area	6-post cab, twi	n doors, flat deck
Steering / seat	Adjustable steering/mech	anical or air suspended seat
Cab suspension	Optional me	chanical system
Dimensions		
Height over cab in. (mm)*	108.5	(2,755)
Overall length in. (mm)	167.5	(4,253)
Wheelbase in. (mm)	97.1	(2,467)
Min. width at fenders in. (mm)	79.3	(2,013)
Weight lbs. (kg)	2wd: 8,426 (3,822)	/ 4wd: 8,978 (4,072)
*Height for standard cab, no susp, flat floor and 16.9R34 tires		

