

Paket opreme	T6010		T6020			T6030		
	Delta	Plus	Delta	Plus	Elite	Delta	Plus	Elite
<b>MOTOR</b>	<b>NEF</b>	<b>NEF</b>	<b>NEF</b>	<b>NEF</b>	<b>NEF</b>	<b>NEF</b>	<b>NEF</b>	<b>NEF</b>
Broj cilindara	4	4	4	4	4	6	6	6
Snaga motora KS(kW)	101(74)	101(74)	112(82)	112(82)	112(82)	117(86)	117(86)	117(86)
Snaga motora sa EPM(power boost-om)KS(kW)	—	—	—	—	132(97)	—	—	142(104)
Okretaji motora (o/min)	2200	2200	2200	2200	2200	2200	2200	2200
Usis (Turbo+Intercooler)	Turbo	•	•	•	•	•	•	•
Broj ventila po cilindru	2	2	2	2	4	2	2	4
Volumen motora (cm <sup>3</sup> )	4485	4485	4485	4485	4485	6728	6728	6728
Okretni moment (Nm)	410@1400	410@1400	510@1250	510@1250	520@1400	522@1250	522@1250	543@1400
Common rail	—	—	—	—	•	—	—	•
Spremnik goriva (l)	176	176	176	176	176	250	250	300
Servisni interval (h)	600	600	600	600	600	600	600	600
<b>MJENJAC</b>								
12x12 Synchro Command™ - meh. revezor	•	—	•	—	—	•	—	—
20x20 Synchro Command™ - pužnim brzinama	◦	—	◦	—	—	◦	—	—
Min. brzina/ s pužnim brzinama (km/h)	2.0/0,2	—	2.0/0,2	—	—	2.0/0,2	—	—
24x24 Dual Command™ - elektro-hidr. reverz.	◦	•	◦	•	—	◦	•	—
48x48 Dual Command™ - pužnim brzinama	◦	◦	◦	◦	—	◦	◦	—
Min. brzina/ s pužnim brzinama (km/h)	1,64/0,16	1,64/0,16	1,64/0,16	1,64/0,16	—	1,64/0,16	1,64/0,16	—
16x16 Electro Command™ - elektro-hidr. reve.	◦	◦	◦	◦	•	◦	◦	•
16x16 Electro Command™ - AutoShift	—	◦	—	◦	◦	—	◦	◦
32x32 Electro Command™ - pužnim brzinama	◦	◦	◦	◦	◦	◦	◦	◦
Min. brzina/ s pužnim brzinama (km/h)	2.27/0.225	2.27/0.225	2.27/0.225	2.27/0.225	2.27/0.225	2.27/0.225	2.27/0.225	2.27/0.225
17x16 Electro Command™ - Eco	—	—	—	—	◦	—	—	◦
17x16 Electro Command™ - 50 km/h	—	—	—	—	◦	—	—	◦
<b>OSOVINE</b>								
4WD pogon	•	•	•	•	•	•	•	•
TerraGlide™ - suspenzija prednje osovine	—	◦	—	◦	◦	—	◦	◦
Fast Steer™ - sustav upravljanja	—	◦	—	◦	◦	—	◦	◦
Max kut zakrenutosti prednje osovine (°)	55	55	55	55	55	55	55	55
<b>HIDRAULIKA</b>								
Hidraulični krug	otvoreni	zatvoreni	otvoreni	zatvoreni	zatvoreni	otvoreni	zatvoreni	zatvoreni
Max broj distributora straga/bočno	3/2	4/2	3/2	4/2	4/2	3/2	4/2	4/2
Upravljanje hidrauličkim distributorima (ili opcija elektrohidraulično)	mehaničko	mehaničko	mehaničko	mehaničko	mehaničko	mehaničko	mehaničko	mehaničko
Kapacitet hidraulične pumpe/tlak pumpe (l/min)	63	80	63	80	113	63	80	113
Upravljanje stražnjim podiznim polugama (MDC ili EDC)	MDC	MDC ili EDC	MDC	MDC ili EDC	EDC	MDC	MDC ili EDC	EDC
Lift-O-Matic™	•	•	•	•	•	•	•	•
Max podizna moć na kraju stražnjih poluga (kg)	5241	6332	5241	6332	5628	5241	6332	5628
Max podizna moć 610 mm iza kugli poluge (kg)	3341	3762	3341	3762	3783	3341	3762	3783
Prednje podizne poluge	◦	◦	◦	◦	◦	◦	◦	◦
Max podizna moć na kraju prednjih poluga (kg)	3700	3700	3700	3700	3700	3700	3700	3700
Kategorija kopčanja na stražnjim polugama	KAT. 2	Kat. 2 –MDC Kat 2/3N-EDC	KAT. 2	Kat. 2 –MDC Kat 2/3N-EDC	KAT. 2/3N	KAT. 2	Kat. 2 –MDC Kat 2/3N-EDC	KAT. 2/3N
<b>PRIKLJUČNO VRATILO (PV)</b>								
540E/1000 (o/min)	•	•	•	•	•	•	•	•
540/540E/1000 (o/min)	◦	◦	◦	◦	◦	◦	◦	◦
Brzina motora pri 540/540E/1000 (o/min)	1969/1546 /2120	1969/1546 /2120	1969/1546 /2120	1969/1546 /2120	1969/1546 /2120	1969/1546 /2120	1969/1546 /2120	1969/1546 /2120
Prednje PV – 1000 (o/min)	◦	◦	◦	◦	◦	◦	◦	◦
<b>KABINA</b>								
Zračna suspenzija sjedala	◦	◦	◦	◦	•	◦	◦	•
Klima uređaj	◦	•	◦	•	•	◦	•	•
Radio CD MP3	•	•	•	•	•	•	•	•
Teleskopski retrovizori	◦	◦	◦	◦	•	◦	◦	•
Prozirni krovni otvor	•	•	•	•	•	•	•	•
Veličina staklene površine (m <sup>2</sup> )	5,85	5,85	5,85	5,85	5,85	5,85	5,85	5,85
Razina buke (dB)	71	71	71	71	70	71	71	70
<b>DIMENZIJE</b>								
Minimalna širina (mm)	2280	2280	2280	2280	2280	2280	2280	2280
Visina do vrha ispušne cijevi (mm)	2876	2876	2876	2876	2876	2920	2920	2920
Visina do vrha kabine (mm)	2856	2856	2856	2856	2856	2900	2900	2900
Međuosovinski razmak (mm)	2387	2387	2387	2387	2387	2627	2627	2627
Ukupna duljina (mm)	4182	4182	4182	4182	4182	4481	4481	4481
Minimalna težina (kg)	4710	4710	4710	4710	4710	5110	5110	5110

T6040	T6050			T6060	T6070	
Elite	Delta	Plus	Elite	Elite	Plus	Elite
NEF	NEF	NEF	NEF	NEF	NEF	NEF
4	6	6	6	4	6	6
122(90)	127(93)	127(93)	127(93)	132(97)	142(104)	142(104)
142(104)	—	—	152(112)	142(104)	—	167(123)
2200	2200	2200	2200	2200	2200	2200
•	•	•	•	•	•	•
4	2	2	4	4	2	4
4485	6728	6728	6728	4485	6728	6728
563@1400	555@1250	555@1250	593@1400	594@1400	625@1250	613@1400
•	—	—	•	•	—	•
176	250	250	300	176	250	300
600	600	600	600	600	600	600
—	•	—	—	—	—	—
—	◦	—	—	—	—	—
—	2,0/0,2	—	—	—	—	—
—	◦	•	—	—	•	—
—	◦	◦	—	—	◦	—
—	1,64/0,16	1,64/0,16	—	—	1,64/0,16	—
•	◦	◦	•	•	◦	•
◦	—	◦	◦	◦	◦	◦
◦	◦	◦	◦	◦	◦	◦
2.27/0.225	2.27/0.225	2.27/0.225	2.27/0.225	2.27/0.225	2.27/0.225	2.27/0.225
◦	—	—	◦	◦	—	◦
◦	—	—	◦	◦	—	◦
•	•	•	•	•	•	•
—	◦	—	◦	—	◦	◦
—	◦	—	◦	—	◦	◦
55	55	55	55	55	55	55
zavoreni	otvoreni	zavoreni	zavoreni	zavoreni	zavoreni	zavoreni
4/2	3/2	4/2	4/2	4/2	4/2	4/2
mehaničko	mehaničko	mehaničko	mehaničko	mehaničko	mehaničko	mehaničko
113	63	80	113	113	80	113
EDC	MDC	MDC ili EDC	EDC	EDC	MDC ili EDC	EDC
•	•	•	•	•	•	•
5628	5241	6332	5628	5628	6332	5628
3783	3341	3762	3783	3783	3762	3783
◦	◦	◦	◦	◦	◦	◦
3700	3700	3700	3700	3700	3700	3700
KAT. 2/3N	KAT. 2	Kat. 2 –MDC Kat 2/3N-EDC	KAT. 2/3N	KAT. 2/3N	Kat. 2 –MDC Kat 2/3N-EDC	KAT. 2/3N
•	•	•	•	•	•	•
◦	◦	◦	◦	◦	◦	◦
1969/1546/2120	1969/1546/2120	1969/1546/2120	1969/1546/2120	1969/1546/ 2120	1969/1546/ 2120	1969/1546/2120
◦	◦	◦	◦	◦	◦	◦
•	◦	◦	•	•	◦	•
•	◦	•	•	•	•	•
•	•	•	•	•	•	•
•	◦	◦	•	•	◦	•
•	•	•	•	•	•	•
5,85	5,85	5,85	5,85	5,85	5,85	5,85
70	71	71	70	70	71	70
2280	2280	2280	2280	2280	2280	2280
2876	2920	2920	2920	2876	2920	2920
2856	2900	2900	2900	2856	2900	2900
2387	2627	2627	2627	2387	2627	2627
4182	4481	4481	4481	4182	4481	4481
4710	5110	5110	5110	4710	5110	5110