



auto poljostroj d.o.o.

ZAGREB, Svetice 25

tel: 01/2395 703; 01/2444 207













e-mail: prodaja@auto-poljostroj.hr



FARMER

POLJSKA



MODEL		F3-6258	F4-6258	F3-7258	F4-7258	F-7258 TE	F2-8248 PE	F-9258 TE	F5-11272	F5-12272 s	
MOTOR	Proizvođač	 JOHN DEERE	 JOHN DEERE	 JOHN DEERE	 JOHN DEERE	 JOHN DEERE	 MMZ	 JOHN DEERE	 IVECO	 IVECO	
	Snaga	45kW / 61KS	45kW / 61KS	49kW / 66KS	49kW / 66KS	56kW / 76KS	62 kW / 84KS	63kW / 86KS	71kW / 97KS	82kW / 112KS	
	Zapremnina	2440 cm ³	2440 cm ³	2440 cm ³	2440 cm ³	4520 cm ³	4750 cm ³	4520 cm ³	4485 cm ³	4485 cm ³	
	Obrtni moment	227Nm / 1800omin ⁻¹	227Nm / 1800 omin ⁻¹	256Nm / 1800 omin ⁻¹	256Nm / 1800 omin ⁻¹	276Nm / 1700 omin ⁻¹	411Nm / 1400omin ⁻¹	302Nm / 1700 omin ⁻¹	398Nm / 1300 omin ⁻¹	510Nm / 1250 omin ⁻¹	
	Tip	4 cilindra turbo s intercoolerom	4 cilindra turbo s intercoolerom	4 cilindra turbo s intercoolerom	4 cilindra turbo s intercoolerom	4 cilindra turbo	4 cilindra turbo	4 cilindra turbo	4 cilindra turbo	4 cilindra turbo	
	Emisija plinova	TIER IIIA	TIER IIIA	TIER IIIA	TIER IIIA	TIER IIIA	TIER IIIA	TIER IIIA	TIER IIIA	TIER IIIA	
UPRAVLJAČKI MEHANIZAM		Hidraulični									
PREDNJI MOST	Proizvođač	 CARRARO									
	Pogon	4 x 4	4 x 4	4 x 4	4 x 4	4 x 4	4 x 4	4 x 4	4 x 4	4 x 4	
	Uključivanje	Mehaničko					Elektro-hidraulično				
MJENJAČ	Proizvođač	 CARRARO							 ZF		
	Tip	Mehanički (sinhroniziran)							Elektro-hidraulični		
	Brzine	8 x 8	8 x 8	8 x 8	8 x 8	12 x 12	12 x 12	12 x 12	16 x 8	16 x 8	
	Reverser	Mehanički (sinhroniziran)							Elektro-hidraulični		
	Spojnicica	Suha (dvostepena)							Elektro-hidraulična		
KOČNICE		Hidraulične (diskovi potopljeni u ulje)									
HIDRAULIKA	Tip	Univerzalna sa regulacijom, više komandi, raznim brzinama dizanja, blokadom dizanja							Elektro-hidraulični / EHR		
	Protok	47 dm ³ /min	47 dm ³ /min	47 dm ³ /min	47 dm ³ /min	58 dm ³ /min	47 dm ³ /min	58 dm ³ /min	107 dm ³ /min		
	Maksimalan pritisak	180 Bar	180 Bar	180 Bar	180 Bar	180 Bar	180 Bar	180 Bar	180 Bar	180 Bar	
	Vanjski izvodi	2 para	2 para	2 para	2 para	3 para	3 para	3 para	3 para	3 para	
	Sila dizanja	1800 kg					2000 kg			4200 kg	
IZLAZNO VRATILO	Brzina vrtnje	540 / 540E omin ⁻¹					540 / 1000 omin ⁻¹				
	Vrsta	Zavisno i nezavisno									
TEŽINA	Ukupna	2910 kg	3120 kg	2910 kg	3120 kg	3740 kg	3740 kg	3740 kg	4650 kg	4650 kg	
	Po osovinama	1520/1390 kg	1515/1605 kg	1520/1390 kg	1515/1605 kg	1784/1956 kg	1760/1980 kg	1784/1980 kg	2280/2370 kg	2280/2370 kg	
DIMENZIJE	Ukupna dužina	3781 mm	3850 mm	3781 mm	3850 mm	4050 mm	4159 mm	4050 mm	4170 mm	4170 mm	
	Visina	2368-2390 mm	2538-2605 mm	2360-2390 mm	2538-2605mm	2640 mm	2720 mm	2640 mm	2637-2689 mm	2637-2689 mm	
	Širina	1568-2000 mm	1925-2326 mm	1568-2000 mm	1925-2326 mm	1966-2444 mm	1970-2428 mm	1966-2444 mm	1991-2479 mm	1991-2479 mm	
	Min. Odstojanje od tla	360 mm	385 mm	360 mm	385 mm	430 mm	410 mm	410 mm	420 mm	420 mm	
PNEUMATICI	Prednji	280/85 R20	320/70 R24	280/85 R20	320/70 R24	320/70 R24	360/70 R24	360/70 R24	13,6 R24	13,6 R24	
	Zadnji	340/85 R28	16,4 R30	340/85 R28	16,4 R30	16,9 R30	16,9 R24	16,9 R24	18,4 R34	18,4 R34	
D.I.	Min. Radijus okretanja	4,54 m	5,20 m	4,54 m	5,20 m	4,83 m	4,83 m	4,83 m	5,60 m	5,60 m	
	Spremnik goriva	75 L	100 L	75 L	100 L	125 L	125 L	125 L	155 L	155 L	
DODATNA OPREMA	Prednji utezi	•	•	•	•	•	•	•	•	•	
	Stražni utezi	•	•	•	•	•	•	•	•	•	
	Klima	•	•	•	•	•	•	•	•	•	
	Mjenjač (12x12/24x24)	•	•	•	•	•	•	•	-	-	
	Hidraulični sistem prik.	•	•	•	•	•	•	•	•	•	
	Pneumatski sistem prik.	•	•	•	•	•	•	•	•	•	
	Prednja hidrailika	•	•	•	•	•	•	•	•	•	
	Prednja hidraulika i PTO	-	-	-	-	-	-	-	•	•	
Pneumatsko sjedalo	-	•	-	•	•	•	•	•	•		
Dodatni hid. cilindar	-	-	-	-	•	•	•	•	-		