

VALPADANA

VP 7000 IS

VP 7000 AR



ORIGINAL
PASSION



VP 7000

7070 IS AR

7080 IS AR

		(TIER 3)	(TIER 3)
Engine			
constructor		FPT	FPT
direct injection		mechanical	mechanical
model		F5A	F5A
max. power (ISO rating)	HP/kW	65 / 48	75 / 55
rated speed	rpm	2300	2300
max. torque	Nm	265	310
max. torque speed	rpm	1250	1250
displacement	cm ³	3200	3200
cylinders / valves		4Turbo / 8	4Turbo / 8
water cooling		STD	STD
fuel tank capacity	litres	60	60
Reverse shuttle			
control		mechanical	
wet disc clutch		STD	
Transmission			
standard gearbox 16FWD + 16REV		STD	
max. speed 40 km/h		STD	
Power take-off			
control		electrohydraulic	
2 speeds 540/750 rpm		STD	
2 speeds 540/1000 rpm		OPT	
ground speed PTO		STD	
Front axle			
four-wheel drive		electrohydraulic engagement	
max. oscillation angle		± 15 degrees	
electrohydraulic differential locks		STD	
Brakes			
control		hydraulic	
rear wet disc brakes		STD	
front wet disc brakes		STD	
Power lift / Hydraulic system			
rise/lower/float control (STD)		draft and position control (OPT)	
electropneumatic suspension for implements		OPT (only IS)	
lift capacity		kg 2300	
hydraulic pump flow (lift + steering system)		l/min 50 + 31	
standard three-point hitch with quick couplings		2 ^a cat	
2-way adjust. three-point hitch with quick couplings		OPT	
no. 2 rear remote valves (1DE + 1DE Float)		STD	
no. 4 rear remote valves (2DE + 2DE Float)		OPT	
free return		STD	
joystick for proportional control of hydr. system		OPT	
Driving position			
platform suspended on silent-blocks		STD	
automatic reverse drive system		OPT	
sprung seat		STD	
Cab			
enclosed cab heated		OPT	
air conditioning		OPT	
Weights (in running order without driver)			
total	kg	2360 (IS) - 2200 (AR)	
Dimensions			
overhang	mm	1260	
wheelbase	mm	1495	
overall length	mm	3735	
ground clearance	min/max mm	310 / 295	
height to steering wheel	mm	1265	
height to ROPS min/max	min/max mm	2455 / 2425	
track	min/max mm	1106/1490 (IS) - 892/1198 (AR)	
width	min/max mm	1393/1750 (IS) - 1179/1513 (AR)	

key: STD = standard; OPT = option; - = not available

Cod. 6508864M1 01/2014 I.P.
All data and illustrations provided in this brochure are for information purposes only and can be changed without notice.