

ZETOR FORTERRAMO

FORTERRA HSX



PERFORMANCE ENDURANCE TOTAL COST OF OWNERSHIP

Tractor is Zetor since 1946.



FORTERRA HSX STANDARD VERSION

MODEL	Units	100	110	120	130	140	
		ENG	INE				
Stage III A Type		Zetor 1005	Zetor 1305	Zetor 1405	Zetor 1505	Zetor 1605	
Stage III B Type		Zetor 1006	Zetor 1306	Zetor 1406	Zetor 1506	Zetor 1606	
Homologated Power 2000/25 (ISO)	kW/HP	71/96	79/107	86/117	95/130 93/126	100/136	
Rated Speed	rpm	2200					
N Weber		8			1/		
No. of Valves			1	6		16	
No. of Cylinders				4			
Aspiration				turbocharged			
Bore/Stroke	mm			105/120			
Displacement	cm ³			4156			
Max. Toque / Torque	Nime /0/	391/37	440/37	480/37	525/34	570/38	
Reserve (ECE R24)	Nm/%	419/46	440/40	482/37	540/41	572/38	
		TRANSM	ISSION				
Туре			er shuttle wit al or automat				
Shifting			fu	lly synchroniz	ed		
No. of Gears				30/30			
Speed	kph	40					
		P1	0				
Туре		clutch enga	inde/minpe gement selec	endent and gro atble in stage		eimplement	
Rear PTO revolutions	rpm		540/100	0(540E/1000	optional)		
Front PTO revolutions	rpm			1 000			
		HYDRA	ULICS				
Туре		Bosch elec	ctronics with 2	Zetor HitchTro	nic, 2 auxiliar	y cylinders	
Three-point Hitch				category II			
Control				electronic			
Lift Capacity at the End of lower Links	kN		65 in tot	al range, max	imum 70		
Operating Pressure	MPa			20			
Hydraulic Pump Capacity	l/min			70			
Hydraulics Quick Couplings				3 pairs + 1			
Hitch System			quick a	adjustable CB	M hitch		

www.zetor.com

MODEL	Units	100	110	120	130	140
		OTHER SPEC	FICATIONS			
Drive System				4WD		
Steering				hydrostatic		
Travelling/ Parking Brakes			wet, disc, hyd	raulic/mecha	anical control	
Trailer Brakes			option	al (air or hydra	aulics)	
Digital Dashboard				standard		
		DIMEN	SIONS			
Weight	kg			4600		
Length	mm			4770		
Width over rear mudguards	mm			2270		
Height to Exhaust Mouth	mm			2810		
Wheelbase	mm			2490		
Front Wheels			13,6R24		14,9R2	24 disc
Rear Wheels			16,9R38		18,4R3	88 disc

CABIN OPTIONS

CABIN "BASIC"	CABIN "CLASSIC"	CABIN "LUX"	
– seat Grammer st.	– seat Grammer st.,	– seat Grammer pneum.	
– passenger seat	– passenger seat	– passenger seat	
- adjustable steering wheel	– adjustable steering wheel	– adjustable steering wheel	
– rear working lights	– front and rear working lights	– front and rear working lights	
	– airconditioning (optional)	– airconditioning	
	– heated back mirrors and	– heated back mirrors and	
	rear window	rear window	
	– audio installation	– audio installation	
		– radio	

OTHER OPTIONAL EQUIPMENT

- . selection of front and rear tyre sizes
- front and rear weight packages
- charcoal filters
- one or two flashing beacons
- . front three-point hitch

- front PTO with clockwise or counter-clockwise direction of rotation
- broad selection of implement hitches from CBM modular system

110

120

130

140



The most powerful and best-equipped tractor in ZETOR range.



ENGINE

Forterra HSX tractors are equipped with 16-valve engines which are appreciated for their high torque reserve (more than 36 %) and economical qualities thanks to which the 225-liter tank suffices for the whole working day.

GEARBOX

Five-gear gearbox with three-stage Powershift and Powershuttle offers 30 F and R gears and automatic shifting of Powershift. New shifting construction offers lower shifting force for the user.

HYDRAULICS AND PTO

Two auxiliary cylinders of hydraulics ensure evenly spread load of the tractor and lifting power up to 7 000 kg. Forterra HSX models are equipped with the latest technology of HitchTronic automatic regulation of the three-point hitch.

CABIN

Dashboard with LCD display which offers a lot of information for the driver and CAN record electronics which makes its service easy. Safety circuit closer in the driver seat for bigger safety of the operator.

UNDERCARRIAGE

Wide wheelbase for high stability of the tractor and outstanding driving properties even when loaded in heavy terrain.

100

110

140

130

www.zetor.com

zetor@zetor.com

DEALER